



N6162

Two Way Splitter



N6163

Three Way Splitter



N6164

Four Way Splitter



N6166

Six Way Splitter



N6168

Eight Way Splitter



N6172

Two Way Splitter



N6173

Three Way Splitter



N6174

Four Way Splitter



N6176

Six Way Splitter



N6178

Eight Way Splitter

2.4G INDOOR SPLITTERS

- Wide Frequency Band up to 2.4GHz
- All ports DC pass (optional model: N617x/A, one port DC pass, N617x/B, all port DC block);
- Zinc Die case housing, Nickel-plated
- Connector: F Female
- Impedance: 75Ω All Ports

Model	Insertion loss (dB, max)			Isolation (dB, min)			Return loss in (dB, min)			Return loss out (dB, min)		
	5-65 MHz	65-1000 MHz	1-2.4 GHz	5-65 MHz	65-1000 MHz	1-2.4 GHz	5-65 MHz	65-1000 MHz	1-2.4 GHz	5-65 MHz	65-1000 MHz	1-2.4 GHz
N6162/N6172	3.5	4.5	7.2	18	28	18	12	12	13	13	12	12
N6163/N6173	7.5	8.5	12.5	20	25	18	10	10	10	10	10	10
N6164/N6174	7.5	8	12.8	22	27	18	12	12	14	12	14	12
N6166/N6176	11	11	12.8	20	22	18	8	8	9	8	8	9
N6168/N6178	12	12	13.5	24	20	20	10	10	9	12	13	10

TVRO SWITCH



N6220

22k Tone Switch



N6240

DiSEqC Switch

- Wide Frequency Band up to 2.4GHz
- Power passing; DC 500mA
- Impedance: 75Ω All Ports
- Connector: F Female

Switches	Model	Freq (MHz)	Insertion loss (dB)	Switch Mode
22K switch	N6220	950-2400	2	22k tone on/off
DiSEqC switch	N6240	950-2400	3	DiSEqC V2.0

TV/SAT DIPLEXER

- Zinc die cast housing, nickel-plated
- 75 ohm F-(f) connectors



N6901

TV/SAT Diplexer

Model	N6901	
	Terr	SAT
Frequency Range (MHz)	5-860	950-2250
Insertion Loss (dB)	≤2	≤3
Isolation (dB)	≥20	≥18